

A-150-RG, OS A-150-RG

File Number: EX2480

COMPANY

BUCKEYE FIRE EQUIPMENT CO  
110 KINGS RD  
PO BOX 428  
KINGS MOUNTAIN, NC 28086-0428 United States

MODEL INFO

A-150-RG, OS A-150-RG High Flow Extinguisher  
Ammonium Phosphate, Cartridge-activated-type

GENERAL


Min Use Temp, °F (°C)	Min Use Temp, F (C)
--	-65 (-54)

EXTINGUISHER CAPACITY AND MINIMUM TEMPERATURE

Nominal Agent Capacity, lb (kg)
125 (57)

EXTINGUISHER RATINGS

Class A Rating	Class B Rating	Class C Rating	Class K Rating	Marine Rating
30-A	240-B	Yes	No	No



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must

appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."